

STOP OVERCOOLING. START DRYING.

Industry experts agree energy efficient building techniques have reduced air conditioning runtime, resulting in the need for dedicated dehumidification in homes. Overcooling to control relative humidity isn't effective or economical and can lead to comfort and health issues.

Dedicated to better IAQ, Santa Fe Ultra Series dehumidifiers efficiently and effectively protect the home and create a living space that is both healthy and comfortable.

Santa Fe Ultra Series dehumidifiers integrate directly with the HVAC system to provide:

- Dedicated dehumidification for the entire home, regardless of AC runtime
- Fresh air intake/ Outdoor air ventilation
- Superior MERV-13 filtration
- Unmatched Warranty-20 percent longer than any competitor

Santa-Fe dehumidifiers are engineered and assembled in Madison, WI by Therma-Stor LLC.

We take pride in building the highest quality products and stand behind every one. Our legacy of innovation and commitment to excellence for over 40 years is what sets us apart.

Santa Fe Stand-Alone Dehumidifiers



Compact70



Oasis™ 105



Classic



Impact155

Santa Fe Air Purifiers



Portable HEPA + UV



Ceiling HEPA
(Standard and Mini)



SANTA-FE™
INDOOR AIR QUALITY SOLUTIONS

Contact us: Santa-Fe-Products.com or 800-533-7533



SANTA-FE™
INDOOR AIR QUALITY SOLUTIONS

**DEDICATED
DEHUMIDIFICATION**

+

**FRESH AIR
VENTILATION**

+

**SUPERIOR
FILTRATION**

Santa-Fe-Products.com



	Ultra70	Ultra98	Ultra120	Ultra155	Ultra205	Ultra120V	UltraMD33
WATER REMOVAL*	70 PINTS/DAY 8.75 GALLONS/DAY	98 PINTS/DAY 12.25 GALLONS/DAY	121 PINTS/DAY 15.13 GALLONS/DAY	155 PINTS/DAY 19.38 GALLONS/DAY	205 PINTS/DAY 25.63 GALLONS/DAY	124 PINTS/DAY 15.5 GALLONS/DAY	33 PINTS/DAY 4.13 GALLONS/DAY
CURRENT DRAW	5.1 AMPS	5.9 AMPS	7.3 AMPS	8.0 AMPS	13.2 AMPS	5.8 AMPS	2.8 AMPS
EFFICIENCY	5.0 PINTS/KWH	6.1 PINTS/KWH	6.1 PINTS/KWH	7.3 PINTS/KWH	5.7 PINTS/KWH	7.6 PINTS/KWH	4.25 PINTS/KWH
ENERGY FACTOR	2.40 L/KWH	2.95 L/KWH	2.95 L/KWH	3.40 L/KWH	2.70 L/KWH	3.60 L/KWH	2.00 L/KWH
BLOWER	150 CFM @ 0.0" WG 140 CFM @ 0.2" WG 130 CFM @ 0.4" WG	320 CFM @ 0.0" WG 297 CFM @ 0.2" WG 215 CFM @ 0.4" WG	350 CFM @ 0.0" WG 285 CFM @ 0.2" WG 210 CFM @ 0.4" WG	391 CFM @ 0.0" WG 363 CFM @ 0.2" WG 337 CFM @ 0.4" WG	526 CFM @ 0.0" WG 495 CFM @ 0.2" WG 458 CFM @ 0.4" WG	445 CFM @ 0.0" WG 390 CFM @ 0.2" WG 360 CFM @ 0.4" WG	155 CFM @ 0.0" WG
AIR FILTER	MERV-13	MERV-13	MERV-13	MERV-13	MERV-13	MERV-13	WASHABLE
DIMENSIONS	12.00" W 12.00" H 28.00" D	14.50" W 19.50" H 32.38" D	14.38" W 21.00" H 32.19" D	20.25" W 21.75" H 41.50" D	20.25" W 21.75" H 41.50" D	26.75" W 43.50" H 18.75" D	14.19" W 30.00" H 5.75" D
WEIGHT	55 LBS.	81 LBS.	91 LBS.	140 LBS.	140 LBS.	120 LBS.	39 LBS.
SIZING**	UP TO 1,800 FT ²	UP TO 2,300 FT ²	UP TO 3,000 FT ²	UP TO 3,500 FT ²	UP TO 5,000 FT ²	UP TO 3,000 FT ²	UP TO 1,200 FT ²
UNIQUE ATTRIBUTE	SUPERIOR EFFICIENCY +COMPACT SIZE	SUPERIOR EFFICIENCY +COMPACT SIZE	SUPERIOR EFFICIENCY +COMPACT SIZE	PATENTED HEAT EXCHANGE TECHNOLOGY	PATENTED HEAT EXCHANGE TECHNOLOGY	VERTICAL DESIGN + DUAL SUPPLY	INNOVATIVE IN-WALL DESIGN
WARRANTY	6 YEAR PARTS 2 YEAR LABOR	6 YEAR PARTS 2 YEAR LABOR	6 YEAR PARTS 2 YEAR LABOR	6 YEAR PARTS 2 YEAR LABOR	6 YEAR PARTS 2 YEAR LABOR	6 YEAR PARTS 2 YEAR LABOR	4 YEAR PARTS 1 YEAR LABOR

*AT 80°F AND 60% RH

**RECOMMENDED FT² BASED ON 8'-10' CEILINGS

Ultra Series dehumidifiers can be controlled comfortably from the living space using the **Ultra Series DEH3000 Digital Control**. Remote sensing option also available with the Ultra Series DEH3000R.

