

# STOP OVERCOOLING. START DRYING.

Industry experts agree energy efficient building techniques have reduced air conditioning runtime, resulting in the need for dedicated dehumidification in homes. Overcooling to control relative humidity isn't effective, or economical, and can lead to comfort and health issues.

Dedicated to better IAQ, Santa Fe Ultra Series dehumidifiers help to efficiently, and effectively, protect the home and aids in creating a living space that is both healthier and more comfortable.

Santa Fe Ultra Series dehumidifiers integrate directly with the HVAC system to provide:

- Dedicated dehumidification for the entire home, regardless of AC runtime
- Fresh air intake / outdoor air ventilation capable
- Superior MERV-13 filtration
- Unmatched Warranty-20 percent longer than any competitor, and includes the industries only labor warranty!



## Santa Fe Stand-Alone Dehumidifiers



Compact70



Advance90



Impact155



Classic

## Santa Fe Air Purifiers



Portable HEPA + UV



Ceiling HEPA  
(Standard and Mini)



**SANTA-FE™**  
INDOOR AIR QUALITY SOLUTIONS

**DEDICATED  
DEHUMIDIFICATION**

+

**FRESH AIR  
VENTILATION**

+

**SUPERIOR  
FILTRATION**



**SANTA-FE™**  
INDOOR AIR QUALITY SOLUTIONS

Contact us: [Santa-Fe-Products.com](http://Santa-Fe-Products.com) or 800-533-7533



[SANTA-FE-PRODUCTS.COM](http://SANTA-FE-PRODUCTS.COM) | 800-533-7533

TS-1227 03/22 Rev A

**PRODUCT LINE UP**

**Ultra70**  
 4033730

**Ultra98**  
 4034240

**Ultra120**  
 4031957

**Ultra120V**  
 4036400

**Ultra155**  
 4031070

**Ultra205**  
 4031560

TEST CONDITIONS	PERFORMANCE DATA					
#1 - AHAM 80°F/60% @ 0" WC	70 PINTS / DAY 3,074 LATENT CAP. / HR	98 PINTS / DAY 4,304 LATENT CAP. / HR	121 PINTS / DAY 5,270 LATENT CAP. / HR	124 PINTS / DAY 5,446 LATENT CAP. / HR	155 PINTS / DAY 6,807 LATENT CAP. / HR	205 PINTS / DAY 9,003 LATENT CAP. / HR
#2 - DOE 73°F/60% @ 0.2" WC	55 PINTS / DAY 2,415 LATENT CAP. / HR	75 PINTS / DAY 3,294 LATENT CAP. / HR	90 PINTS / DAY 3,953 LATENT CAP. / HR	105 PINTS / DAY 4,611 LATENT CAP. / HR	130 PINTS / DAY 5,709 LATENT CAP. / HR	165 PINTS / DAY 7,246 LATENT CAP. / HR
#3 - MANUAL S 75°F/55% @ 0.2 WC	53 PINTS / DAY 2,328 LATENT CAP. / HR	75 PINTS / DAY 3,294 LATENT CAP. / HR	91 PINTS / DAY 3,996 LATENT CAP. / HR	91 PINTS / DAY 3,996 LATENT CAP. / HR	118 PINTS / DAY 5,182 LATENT CAP. / HR	156 PINTS / DAY 6,851 LATENT CAP. / HR
#4 - MANUAL J 75°F/50% @ 0.2" WC	42 PINTS / DAY 1,845 LATENT CAP. / HR	65 PINTS / DAY 2,833 LATENT CAP. / HR	78 PINTS / DAY 3,426 LATENT CAP. / HR	86 PINTS / DAY 3,777 LATENT CAP. / HR	109 PINTS / DAY 4,765 LATENT CAP. / HR	129 PINTS / DAY 5,665 LATENT CAP. / HR
#5 - 70°/50% @ 0.2" WC	34 PINTS / DAY 1,493 LATENT CAP. / HR	55 PINTS / DAY 2,415 LATENT CAP. / HR	66 PINTS / DAY 2,899 LATENT CAP. / HR	76 PINTS / DAY 3,338 LATENT CAP. / HR	96 PINTS / DAY 4,216 LATENT CAP. / HR	114 PINTS / DAY 5,007 LATENT CAP. / HR
<b>MAXIMUM RECOMMENDED VENTILATION AIR</b>	50 CFM	106 CFM	116 CFM	147 CFM	129 CFM	174 CFM
<b>CURRENT DRAW @ Test Condition #1</b>	5.1 AMPS	5.9 AMPS	7.3 AMPS	5.8 AMPS	8.0 AMPS	13.2 AMPS
<b>EFFICIENCY @ Test Condition #1</b>	5.0 PINTS/KWH	6.1 PINTS/KWH	6.1 PINTS/KWH	7.6 PINTS/KWH	7.3 PINTS/KWH	5.7 PINTS/KWH
<b>BLOWER</b>	150 CFM @ 0.0" WC 140 CFM @ 0.2" WC 130 CFM @ 0.4" WC	320 CFM @ 0.0" WC 297 CFM @ 0.2" WC 215 CFM @ 0.4" WC	350 CFM @ 0.0" WC 285 CFM @ 0.2" WC 210 CFM @ 0.4" WC	445 CFM @ 0.0" WC 390 CFM @ 0.2" WC 360 CFM @ 0.4" WC	391 CFM @ 0.0" WC 363 CFM @ 0.2" WC 337 CFM @ 0.4" WC	526 CFM @ 0.0" WC 495 CFM @ 0.2" WC 458 CFM @ 0.4" WC
<b>AIR FILTER</b>	MERV-13	MERV-13	MERV-13	MERV-13	MERV-13	MERV-13
<b>DIMENSIONS</b>	12"Wx12"Hx28"D	14.50"Wx19.50"Hx32.375"D	14.375"Wx21"Hx32.1875"D	26.75"Wx43.50"Hx18.75"D	20.25"Wx21.75"Hx41.50"D	20.25"Wx21.75"Hx41.50"D
<b>WEIGHT</b>	55 LBS.	81 LBS.	91 LBS.	120 LBS.	140 LBS.	140 LBS.
<b>WARRANTY</b>	6 YEAR PARTS 2 YEAR LABOR	6 YEAR PARTS 2 YEAR LABOR	6 YEAR PARTS 2 YEAR LABOR	6 YEAR PARTS 2 YEAR LABOR	6 YEAR PARTS 2 YEAR LABOR	6 YEAR PARTS 2 YEAR LABOR

Santa Fe Ultra Series dehumidifiers can be controlled comfortably from the living space using the **UltraDEH 3000 Digital Control**. Remote sensing option also available with the **UltraDEH 3000R**.


**UltraMD33**  
 4035900

**PERFORMANCE DATA**  
 (UltraMD33 is not ductable)

**MAXIMUM RECOMMENDED VENTILATION AIR**   **CURRENT DRAW**   **EFFICIENCY**   **BLOWER**   **AIR FILTER**   **DIMENSIONS**   **WEIGHT**   **WARRANTY**

#1 - AHAM - 33 PINTS / DAY/1,449 LATENT CAP. / HR	N/A	2.8 AMPS	4.25 PINTS/KWH	155 CFM @ 0.0" WC	WASHABLE	14.1875"W x 30"H x 5.75"D	39 LBS.	4 YEAR PARTS 1 YEAR LABOR
#2 - DOE 73°F/60%RH - 26 PINTS / DAY/1,145 LATENT CAP. / HR								
#3 - MANUAL S - 24 PINTS / DAY/1,054 LATENT CAP. / HR								
#4 - MANUAL J - 18 PINTS / DAY/791 LATENT CAP. / HR								
#5 - 14 PINTS / DAY/615 LATENT CAP. / HR								